

Declaration of Performance

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Francois Grimal, Chairman of the board
Frøstrup d. 31/3-15



Signature

Place and date

Declaration of conformity:

Dolle Modular staircases:

Barcelona

is designed and manufactured according to ETAG 008:2001 part 1.

Material and manufacturing of the staircase complies to ETA 07/0238 from 28. September 2011.

Dolle Suzhou Indu. Co. LTD is certified by inspection of FPC system based on ETAG 008:2002 and ETA 07/0238. The FPC system is under continuously surveillance, assessed and approved by ITeC (Institut de Tecnologia de la Construcció de Catalunya). Furthermore compliance to ETAG 008:2002 part 1 is declared by this document and by CE-marking of the products in accordance to ETA 07/0238 section 3.

Reaction to fire class F – no performance determined.

31-03-2015



Francois Grimal

Chairman of Dolle Suzhou Indu. CO. LTD

1. Building material category:

Prefabricated stair kit

2. Building material identification:

ETA 07/0238 Spiral staircases

Product name: Barcelona (Trade name: Charleston)

Dolle A/S product number: 68730 AL

3. Intended use or uses of the construction product:

Dolle Spiral modular are defined as means of internal access under the category "floors" because this type of staircase is for use in private homes as opposed to stairs, which are used as external access in larger building complexes.

The staircases are meant to be used as secondary access ways.

4. Name and contact address of the manufacturer:

Dolle Suzhou Indu. CO. LTD

32 Yongfang Rd., Huangqiao Street

XiangCheng District

215132 SUZHOU, Jiangsu, China

5. Name and address of authorized representative: Not available.

6. System of assessment and verification of constancy of performance of construction product: System 2+

7. Not available.

8. ETA Danmark

Issued Technical Approval: ETA 07/0238

on the basis of Technical Approval Guideline:

ETAG 008:2002



2292

Dolle Suzhou Indu. CO. LTD
32 Yongfang Rd., Huangqiao Street
XiangCheng District
215132 SUZHOU, Jiangsu, China

15

2292/CPR/4293

Notified body:

ITeC – The Catalonia Institute of Construction Technology

Wellington 19 - E08018 Barcelona - Tel 933 093 404

fperez@itec.cat - www.itec.cat

Performed assessment and verification of constancy of performance described in the ETA 07/01238 under system 2+

And issued certificate of conformity of the factory production control:

1220-CPR-1211

Essential characteristics	Performance	Reference to ETAG and/or ETA
Steps • E0 • Gmean • fm,k • Fv,k • γM	Plywood 10000 [N/mm ²] 600 [N/mm ²] 30 [N/mm ²] 3 [N/mm ²] 1,5	ETAG 008 and ETA 07/0238
Centrepost, Railings, Fixings • E • G • Fy,k • Fu,k • γM	S275 210000 [N/mm ²] 81000 [N/mm ²] 275 [N/mm ²] 410 [N/mm ²] 1,1	ETAG 008 and ETA 07/0238
Load/displacement behaviour and vibration behaviour (dead load/single load of F = 1,0 kN): Deflection max Frequency	Determined by assessment W≤5 mm ≥ 5 Hz.	ETAG 008 and ETA 07/0238
Load bearing capacity ultimate limit state: Flight: vertical distributed load Step: vertical single load Handrail: Horizontal line load γm	 4,6 kN/m ² 3,55 kN 1,09 kN/m 1,1	ETAG 008 and ETA 07/0238 EN 1991-1-1

Load bearing capacity at serviceability limit state: • Deflection of the flight under service load (uniformly distributed load) Load Fs • Deflection under service load related to the median line of the flight • Deflection of step under service load (P) (point load) Load Fs • Deflection under service load related to the length of the centre post • Length of the centre post	p: 2,2 kN/m ² W: L/200 P: 2,5 kN W: L/100 L: 2912 mm	ETAG 008 and ETA 07/0238 EN 1991-1-1
Load bearing capacity – Service loads Vertical variable uniformly distributed load q Vertical variable single load Q	2,2 kN/m ² 2,2 Kn	ETAG 008 and ETA 07/0238
Resistance to earthquakes	NPD	ETAG 008 and ETA 07/0238
Resistance of the fixing	NPD	ETAG 008 and ETA 07/0238
Reaction to Fire	Class F	ETAG 008 and ETA 07/0238
Fire resistance	NPD	ETAG 008 and ETA 07/0238
Hygiene, health and environment	Does not contain classified substances. Class E1	Regulation 1272/2008 and EN 13986
Slipperiness	NPD	ETAG 008 and ETA 07/0238
Impact resistance	NPD	ETAG 008 and ETA 07/0238
Resistance to deterioration caused by physical, chemical and biological agents	Resistant	ETAG 008 and ETA 07/0238

9. The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8.